

# PFINDER 902

## PENETRANT FLUORESCENT

### Type I | sensitivity level 2



Version 14 | 01.07.2022 | Page 1/1

#### DESCRIPTION

PFINDER 902 is a hydrocarbon-free, directly water-washable fluorescent penetrant for crack detection of surfaces. PFINDER 902 is readily biodegradable according to ISO 9888 / Zahn-Wellens-EMPA test (OECD 302 B). Details and test report available on request.

Due to its removability PFINDER 902 provides only a low residual background even on rough surfaces and therefore a user-friendly interpretability of the indications.

PFINDER 902 is qualified for penetrant testing at temperatures up to + 100 °C (temperature of work part) according to EN ISO 3452-5.

Penetrant type I according DIN EN ISO 3452-1.  
Use: Type I, Method A, C, E, Form a, b, c, d, f, g.

#### APPLICATION

The capability of the penetrant system should be checked regularly by means of own reference pieces or e.g. reference test block 2 according EN ISO 3452-3.

Process description according DIN EN ISO 3452-1 see [www.pfinder.com](http://www.pfinder.com).

For applications at temperatures above + 50 °C, penetration time has to be adapted as follows:

- + 100 °C to + 50 °C: penetration time up to 15 minutes
- + 50 °C to + 10 °C: according DIN EN ISO 3452-1 and EN ISO 3452-2

Values are referring to the temperature of the working part. Aerosol spray cans must not be warmed up above + 50 °C.



#### YOUR GREEN NDT BENEFITS

- | Readily biodegradable – no waste water treatment required
- | Nearly odourless
- | Free of aromatics, hydrocarbons and heavy metals



#### YOUR HANDLING + COST SAVING BENEFITS

- | Bright, sharp indications with high contrast
- | Easy rinsability = low background fluorescence
- | Reduced consumption due to low viscosity

#### APPROVALS & CONFORMITIES

The product conforms to these specifications / is suitable for the use according to:

EN ISO 3452-2 | 3452-5 |  
VDA236-150 | ASTM E165 |  
ASTM E1417 | ASME V Art. 6

Low content of sulfur and halogens according to EN ISO 3452-2.

#### PACKAGING

500-ml-spray can (for 360° application) | 5-l-canister | 30-l-canister |  
200-l-drum | 1000-l-container

These packages are on stock and instantly available. Other packages on demand.

#### SHELF-LIFE & STORAGE

3 years  
Storage between + 5 °C and + 45 °C.

CHARACTERISTIC DATA	Specification	Unit	Value
Density/20 °C	DIN 51757	kg/m <sup>3</sup>	952 ± 48
Viscosity/20 °C	ASTM D7042	mm <sup>2</sup> /s	approx. 16
Flash Point	EN ISO 2719	°C	≥ 109

Data of products packaged in aerosol spray cans might differ.